

NON-METALLIC SEALTITE® SERIES

SEALTITE® CNP (TYPE A) NON-METALLIC ROBOTIC FLEXIBLE CONDUIT



DESCRIPTION

- Non-metallic Type A liquid-tight conduit
- Great for constantly flexing applications
- Good for abrasion and where physical abuse may exist
- Standard in orange
- Also available in grey by special order
- Uses Type A Connector only

SPECIFICATIONS

- Smooth inner PVC core with outer oil resistant PVC cover bonded together with nylon reinforcing braid
- Colour: orange
- Temperature range: -20°C to 60°C (-4°F to +140°F)
- UV (sunlight) resistant, Flame retardant
- Oil resistant
- CSA Approved #LL15275-10
- UL Approved #E75863

APPLICATIONS

- Automotive applications requiring continuous flexing
- Food machine applications where non-metallic and flexing required



Trade Size	Item ID	Std. Pkg. m (ft)	Inside Diameter Min	Outside Diameter		Bend Radius	Weight kg/m (lbs/cft)
				Min	Max		
3/8" (12)	38602	30 (100)	12.32 (0.485)	19.20 (0.755)	19.68 (0.775)	64 (2.5)	0.22 (15)
	38601	76 (250)					
1/2" (16)	38612	30 (100)	15.75 (0.620)	23.11 (0.910)	23.62 (0.930)	76 (3.0)	0.31 (21)
	38611	61 (200)					
	38613	243 (800)					
3/4" (21)	38622	30 (100)	20.70 (0.815)	29.21 (1.150)	29.72 (1.170)	102 (4.0)	0.45 (30)
	38621	53 (150)					
	38623	243 (800)					
1" (27)	38631	30 (100)	26.16 (1.030)	35.94 (1.415)	36.57 (1.440)	153 (6.0)	0.64 (43)
	38633	152 (500)					
1-1/4" (35)	38641	15 (50)	34.79 (1.370)	45.72 (1.800)	46.35 (1.825)	178 (7.0)	0.86 (58)
	38643	61 (100)					
1-1/2" (41)	38651	15 (50)	40.26 (1.585)	51.94 (2.045)	52.83 (2.080)	178 (7.0)	1.21 (81)
	38653	30 (100)					
2" (53)	38661	15 (50)	51.94 (2.045)	66.17 (2.605)	67.06 (2.640)	229 (9.0)	1.82 (122)
	38663	30 (100)					

All dimensions in mm (inches) unless stated

FITTINGS FINDER



PAGE 53