



Sealtite Type NMUA (Type B): Non-metallic Flexible Conduit

NMUA:



Co-extruded spiral with smooth inner and outer walls

Trade	Item	Std. Pkg.	Inside Diameter	Outside Diameter		Bend	Weight
Size	ID	METERS	Min	Min	Max	Diameter	Kg/m (lbs/cft)
3/8" (12)	39302	30	12.29 (0.484)	17.53 (0.690)	18.03 (0.710)	102 (4.0)	0.17 (11)
1/2" (16)	39312	30	15.80 (0.622)	20.83 (0.820)	21.34 (0.840)	165 (6.5)	0.23 (15)
	39313	150					
	39314	300					
3/4" (21)	39322	30	20.83 (0.820)	26.16 (1.030)	26.67 (1.050)	216 (8.5)	0.30 (20)
	39323	150					
1" (27)	39331	30	26.44 (1.041)	32.77 (1.290)	33.40 (1.315)	330 (13.0)	0.40 (27)
1-1/4" (35)	39341	15	35.05 (1.380)	41.40 (1.630)	42.16 (1.660)	406 (16.0)	0.53 (36)
1-1/2" (41)	39353	15	40.01 (1.575)	47.37 (1.865)	48.26 (1.900)	457 (18.0)	0.67 (45)
2" (53)	39361	15	51.31 (2.020)	59.44 (2.340)	60.33 (2.375)	564 (22.2)	1.00 (67)
2-1/2" (63)	39371	8	62.99 (2.480)	72.10 (2.840)	73.00 (2.875)	635 (25.0)	1.35 (91)

* 2-1/2" is not CSA or UL Approved. All dimensions in mm (inches)

AC Whip Kits:



Trade	Item ID	Length	Connectors	Wire
Size	Kit	Conduit	Included	Gauge
1/2"	WK5042	4ft	1xStr, 1x90°	3 x #10
1/2"	WK5062	6ft	1xStr, 1x90°	3 x #10
1/2"	WK5082	8ft	1xStr, 1x90°	3 x #10
3/4"	WK7542	4ft	1xStr, 1x90°	2 x #8, 1 x #10
3/4"	WK7562	6ft	1xStr, 1x90°	2 x #8, 1 x #10
3/4"	WK7582	8ft	1xStr, 1x90°	2 x #8, 1 x #10

All dimensions in mm (inches)

Sealtite Type NMUA :



- Non-metallic Type B liquid-tight conduit
- Designed for standard commercial and industrial applications
- Approved in US (per NEC) for direct burial applications
- Also available by special order in other colours. (consult factory)
- Uses special non-metallic connectors for easy installation. Can also be used with standard liquid-tight connector.
- Available in custom cut lengths

For connectors for this conduit, see page 26 (or 19-20)
For cutting instructions, see page 37
For Chemical Resistance, see page 38

SPECIFICATIONS:

- Co-extruded PVC conduit.
- Colour: Grey
- Temp. range: -18°C to +80°C (0°F to +176°F) Dry
Wet: +60°C (+140°F)
Oil: +70°C (+158°F)
- UV (sunlight) Resistant
- Oil Resistant
- CSA Approved: # 20817
- UL Approved: # E211327

KITS:

- Kits assembled with CSA/UL approved components.

APPLICATIONS:

- HVAC industry
- Commercial and industrial applications requiring UL & CSA Approvals.